



### GAS LEAK DETECTOR 7201 AT A GLANCE

- DETECTS METHANE AND PROPANE GAS LEAKAGE !
- SINGLE COLOR LED DISPLAY 5-LEVEL LEAK !
- ALARM AND READY LED !
- BATTERY LOW INDICATION !
- AUTO-CALIBRATION WHILE POWERS ON !
- BUILT IN EARPHONE JACK !
- FEATURES MUTE FUNCTION !
- QUALITY SEMI-CONDUCTOR SENSOR !
- QUICK RESPONSE !
- 35-40PPM SENSITIVITY



### FEATURE

<input checked="" type="checkbox"/>	Quick to pinpoint gas leaks.
<input checked="" type="checkbox"/>	Auto power off preserves remaining battery life.
<input checked="" type="checkbox"/>	DC/AC 2-way power system for operation .
<input checked="" type="checkbox"/>	8 LED lights indicate 40ppm, 80ppm, 160ppm, 320ppm and 640ppm for Propane ; 120ppm, 240ppm, 480ppm, 960ppm and 1920ppm for Methane.
<input checked="" type="checkbox"/>	When power is on ,ready LED is off . LED is on after warm up time ( < 60seconds).
<input checked="" type="checkbox"/>	Response time less than 2 seconds.
<input checked="" type="checkbox"/>	High sensitivity features an audio mute switch button to silence the unit.
<input checked="" type="checkbox"/>	Pinpoint gas leak with a 18" flexible probe in hard-to-rech areas.
<input checked="" type="checkbox"/>	Detect Natural gas or propane fired heating system or gas pipelines.

### SPECIFICATION

<b>▲ Detect range:</b> Methane: 120ppm - 1920 ppm	<b>▲ Warm-up time:</b> < 60 seconds
Propane : 40ppm - 640ppm	<b>▲ Response time:</b> < 10 seconds
<b>▲ Model 7201 :</b> Filter included for high discrimination.	<b>▲ Sensitivity:</b> 40ppm
<b>▲ Operating temperature range:</b> -5~45°C	<b>▲ Dimension:</b> 175 x 70 x 38mm(HxWxT)
<b>▲ Flexible probe 18" (465mm ) length:</b>	<b>▲ Indicator:</b> Acoustic intermittent beep & LEDs.
<b>▲ Auto power off timeout:</b> About 10 minutes	<b>▲ Battery:</b> 4 pcs of AA
	<b>▲ Standard packing includes::</b> Meter, stainless flexible probe , batteries instruction manual